



150NCT

Mounted on tractor

The Thomas boomlift, type **150NCT-15M** work height, is a semi-professional boom lift, consisting of a telescopic arm. The telescopic arm is installed on a 360° rotating tower. The unit is installed on a very sturdy and stable base with two hydraulic support feet HE (telescopically extendable support feet). This machine is mounted on a standard tractor from 4000kg. The big advantage of this machine is the **fast assembly & disassembly thanks to our Thomas quick-change system, three-point assembly/disassembly in five minutes.**

Description	Technical Data	Work Diagram	Options	Applications
<ul style="list-style-type: none"> • 2-value load moment (200NCTJ... 300NCTJ) • Acoustic signal for tilt adjustment • Hour meter • Explosion-proof design • PVC basket • Rotatable basket (2 x 70 ° 120NCT... 180NCTJ) • Rotatable basket (2 x 90 ° 200NCTJ-300NCTJ) • Diesel version • Petrol version • 1000V insulation 				



Interior such as:

- Working in sports halls
- Working in churches
- Working in commercial buildings
- Working in halls
- Etc.

Outdoor work such as:

- Maintenance works
- Cleaning works
- Paintwork
- Facade works
- Roofing
- Chimney works
- Pruning
- Installing solar panels
- Placing pipes in chimneys
- Placing Christmas and other lights
- Placing publicity signs and posters
- Etc.

Description	Technical Data	Work Diagram	Options	Applications
Working height:	15m			
Platform height:	13m			
Outreach:	10,6m			
Platform capacity:	200kg			
Rotation:	360°			
Weight:	1800kg			
Transportation height:	3,4m			
Transportation length:	3,22m			
Width transportation:	Tractor width			
Width working position:	Tractor width + 700mm			
Power (mono):	12V			
Operation:	Electro-hydraulic			
Fuel:	Diesel + PTO			
Basket:	ALU			
Minimum tractor weight:	4000kg			